

SONIC LINE

the most versatile turntable stretch wrapper

HIGH-PROFILE SEMI-AUTOMATIC



SONIC HPX ▶

The X-TRETCH pre-stretch film carriage provides superior film economy, film tension and user safety.

- ✓ Uses 20" machine film
- ✓ Electronically adjustable film tension
- ✓ 250% film pre-stretch ratio, others available
- ✓ Maintenance free ball bearing carriage guide
- ✓ Automatic corner compensation
- ✓ Lifetime warranty on stretch rollers

The Robust PRO-GLIDE turntable support system is maintenance free and features superior weight capacity.

- ✓ Structural steel frame
- ✓ Forklift portable
- ✓ Flush with floor pit mountable
- ✓ Easy access to components
- ✓ 1/2 HP turntable drive motor
- ✓ Heavy duty turntable chain drive

The advanced and user-friendly DIGI-TECH control unit features unique functions to wrap any type of pallet


- ✓ Photo-eye automatic height detection
- ✓ Separate top and bottom wrap count 1-10
- ✓ Turntable soft start/stop
- ✓ Dual adjustable film carriage speed
- ✓ Reinforce wrap function
- ✓ Positive turntable home alignment
- ✓ Gentle wrap feature for light or unstable pallets

POPULAR OPTIONS

- Wrap height extension for taller pallets
- Frame extension for larger than standard pallets
- Split base for variable pallet size
- 30" film carriage
- Turntable weight capacity increase
- Scale package with digital weight indicator
- Auto film cut
- 59" diameter turntable

TECHNICAL SPECIFICATIONS

➤ Turntable Speed	Adjustable up to 16 RPM
➤ Control Type	Full-Feature Semi-Automatic
➤ Max. Load Capacity	5,000 lbs
➤ Max. Load Height	80"
➤ Turntable Size	48" x 48" octagonal
➤ Turntable Height	9" from floor
➤ Pre-Stretch Ratio	250% standard
➤ Max. Load Size	56" x 56"
➤ Electrical	115/1/60 15 amp
➤ Warranty	3/5 years
➤ Tower Height	85"
➤ Clearance Required	97"



SONIC HPX

Mach 1