

# GW-1200



# GW-1200

Economical semi-automatic turntable wrapping machines are reliable, safe and easy to use.



## Efficiency

- Adjustable film-tension control
- Minimum consumption of film per pallet
- Optimization of cost per pallet

## Safety

- Film carriage inside the tower
- Safe, fast and ergonomic film loading
- Safety switch for film loading door
- Emergency stop




## Easy to use

- Adjustable number of top and bottom wraps
- Adjustable carriage and turntable speed
- Reinforcing wrap function
- Soft START/STOP
- Load begins and ends in same position
- Adjustable overwrap



## Simplicity

- Fast and simple installation
- Safe transportation (machine packed in a wooden crate)
- Easy maintenance
- Height sensing by photocell (wrapping of dark colored goods also possible)
- Easy film feeding – the film is just placed in the middle of the carriage and threaded through the threading slot



## Options

- Access ramp
- Optional scale



## Oriented Machine Film Benefits

- No waste due to knicked edges
- Guaranteed film consistency
- Ready to be applied with minor tension. No need to be pre-stretched.
- Consistent Film Delivery
- No Pre-Stretch carriage maintenance

## Technical data

<b>Capacity</b>	Up to 35 pallets/hr (depending on pallet dimensions)
<b>Power supply</b>	120V, single phase, 60Hz
<b>Turntable speed</b>	2-12 rpm
<b>Turntable height</b>	3 1/4"
<b>Film carriage</b>	variable up/down speed
<b>Machine dimensions:</b>	100" x 65"
<b>Turntable Ø:</b>	65"
<b>Space required:</b>	45.6 ft <sup>2</sup> (height 114")
<b>Machine weight:</b>	approx. 950 lbs.
<b>Wrapping height:</b>	90"
<b>Max. pallet weight:</b>	4,400 lbs.
<b>Pallet dimensions:</b>	65"L x 65"W x 90"H (max)

